## NSN 5340-01-201-2660

Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-201-2660

| ·   |
|---|
| Thread Class:   |
| 2b left internal (includes through thread)2a right external                     |
| Thread Direction:   |
| Right-hand right external   |
| Thread Length:  |
| 0.203 inches left internal (includes through thread)0.181 inches right external |
| Shoulder Diameter:  |
| 0.125 inches  |
| Shoulder Length:  |
| 0.281 inches  |
| Length:   |
| 0.551 inches  |
| Thready Qty Per Inch (tpi):   |
| 56 left internal (includes through thread)                                      |
| Thread Size:  |
| 0.086 inches right external   |
| Material:   |
| Steel comp 303 standoff   |
| Material Specification:   |
| Astm a582 assn standard single material response standoff                       |
| Surface Treatment:  |
| Passivate standoff  |
| Surface Treatment Specification:  |
| Qq-p-35 type iv federal specification single treatment response standoff        |
| Thread Series Designator:   |
| Unc right external  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| -   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A08900  |
|   |