

View Online at <https://aerobasegroup.com/nsn/5340-01-202-6022>

**First Leg Length:**

Between 0.780 inches and 0.820 inches

**Second Leg Length:**

Between 3.365 inches and 3.405 inches

**Second Leg Width:**

Between 1.220 inches and 1.300 inches

**First Leg Hole Diameter:**

Between 0.200 inches and 0.210 inches

**Second Leg Hole Diameter:**

Between 0.274 inches and 0.288 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.760 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.130 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.230 inches and 0.270 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.230 inches and 0.270 inches

**First Leg Thickness:**

Between 0.060 inches and 0.066 inches

**Second Leg Thickness:**

Between 0.060 inches and 0.066 inches

**First Leg Width:**

Between 0.230 inches and 0.270 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.230 inches and 0.270 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.195 inches and 0.205 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Angle

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

Between 38.0 degrees and 42.0 degrees

**Material:**

Steel

**Material Specification:**

Ams 5599 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0