

View Online at <https://aerobasegroup.com/nsn/5340-01-202-7739>

Cross Sectional Shape:

Flat, square or rectangular rib reinforced

Hole Diameter:

0.180 inches

Width:

Between 4.760 inches and 4.800 inches

Flange Thickness:

0.125 inches

Edge Shape:

Rectangle, four holes

Length:

Between 5.540 inches and 5.580 inches

Corner Radius:

0.060 inches

Distance Between Holes Along Length:

Between 5.110 inches and 5.115 inches

Distance Between Holes Along Width:

Between 4.330 inches and 4.335 inches

Distance From First Hole Centerline To End Along Length:

0.130 inches

Distance From First Hole Centerline To End Along Width:

0.130 inches

Body Thickness:

0.355 inches

Securing Device Type:

Special

Mounting Opening Shape Style:

Unthreaded hole

Special Features:

Finish, color white 27875; 4 holes, 0.180 dia, csk 100 degrees by 0.344 diameter reverse side; used in power supply on m551

Material:

Aluminum alloy 356.0

Material Specification:

Mil-c-11866, comp 2 military specification single material response

Surface Treatment:

Enamel semigloss

Surface Treatment Specification:

Mil-c-5541, class 1a military specification 1st treatment response and tt-p-636 federal specification 2nd treatment response or tt-p-664 federal specification 2nd treatment response and tt-e-529 federal specification 3rd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A531c0

Mil-std (military Standard):

Mil-c-11866 spec.