

View Online at <https://aerobasegroup.com/nsn/5340-01-204-2694>

First Leg Length:

2.380 inches

Second Leg Length:

3.430 inches

Second Leg Width:

5.750 inches

First Leg Hole Diameter:

0.623 inches

Second Leg Hole Diameter:

1.060 inches

Second Leg Distance From Edge To Hole Center Along Width:

4.436 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.710 inches

First Leg Thickness:

0.500 inches

Second Leg Thickness:

0.500 inches

Center Section Height:

5.000 inches

Center Section Width:

Between 4.000 inches and 5.750 inches

Center Section Thickness:

0.500 inches

First Leg Width:

4.000 inches

First Leg Distance Between Hole Centers Along Width:

2.126 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.880 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 1015 or steel comp 1025

Material Specification:

Astm-a108 assn standard 1st material response or astm-a576 assn standard 2nd material response

Surface Treatment:

Phosphate

Surface Treatment Specification:

Mil-p-16232 type m or z, cl 2 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-p-16232 spec.