

View Online at <https://aerobasegroup.com/nsn/5340-01-204-3905>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.170 inches

**Second Leg Length:**

1.270 inches

**Second Leg Width:**

3.800 inches

**Second Leg End Width:**

3.600 inches

**First Leg Hole Diameter:**

0.165 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.440 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.760 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.630 inches

**Second Leg Slot Length:**

0.780 inches

**Second Leg Slot Width:**

0.280 inches

**First Leg Thickness:**

0.060 inches

**Second Leg Thickness:**

0.060 inches

**First Leg Width:**

3.800 inches

**First Leg End Width:**

2.270 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

0.720 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

0.720 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.600 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.550 inches

**First Leg Style:**

Angle

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Angle

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 6061

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.