

View Online at <https://aerobasegroup.com/nsn/5340-01-204-3905>

Mounting Hole Type:

Plain

First Leg Length:

1.170 inches

Second Leg Length:

1.270 inches

Second Leg Width:

3.800 inches

Second Leg End Width:

3.600 inches

First Leg Hole Diameter:

0.165 inches

Second Leg Distance Between Hole Centers Along Width:

1.440 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.760 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.630 inches

Second Leg Slot Length:

0.780 inches

Second Leg Slot Width:

0.280 inches

First Leg Thickness:

0.060 inches

Second Leg Thickness:

0.060 inches

First Leg Width:

3.800 inches

First Leg End Width:

2.270 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.720 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

0.720 inches

First Leg Distance From Edge To Hole Center Along Width:

1.600 inches

First Leg Distance From Edge To Hole Center Along Length:

0.550 inches

First Leg Style:

Angle

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Angle

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.