

View Online at <https://aerobasegroup.com/nsn/5340-01-205-5120>

**Mounting Hole Type:**

Countersunk and plain

**First Leg Length:**

1.380 inches

**Second Leg Length:**

5.250 inches

**Reinforcement Method (non-core):**

Gusset both legs

**Second Leg Width:**

1.250 inches

**Second Leg End Width:**

0.560 inches

**First Leg Hole Diameter:**

Between 0.197 inches and 0.204 inches

**Second Leg Hole Diameter:**

Between 0.197 inches and 0.204 inches

**Second Leg Distance Between Hole Centers Along Length:**

2.320 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.280 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.310 inches

**First Leg Thickness:**

0.090 inches

**Second Leg Thickness:**

0.090 inches

**First Leg Width:**

1.250 inches

**First Leg Distance Between Hole Centers Along Width:**

0.380 inches

**First Leg Distance Between Hole Centers Along Length:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.440 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.380 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Color gray; all holes to be free of paint and primer

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8, h32 federal specification single material response

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

6032465-12 fscm 03640 mfr ref single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0