

View Online at <https://aerobasegroup.com/nsn/5340-01-205-5123>

Mounting Hole Type:

Plain

First Leg Length:

1.680 inches

Second Leg Length:

2.520 inches

Second Leg Width:

2.360 inches

First Leg Slot Length:

0.219 inches

First Leg Slot Width:

0.188 inches

Second Leg Hole Diameter:

1.562 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.180 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.180 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

2.810 inches

First Leg End Width:

2.370 inches

First Leg Distance Between Hole Centers Along Width:

0.438 inches

First Leg Distance Between Hole Centers Along Length:

0.812 inches

First Leg Distance From Edge To Hole Center Along Width:

1.186 inches

First Leg Distance From Edge To Hole Center Along Length:

0.6875 inches

Second Leg End Radius:

1.180 inches

First Leg Style:

Corner radius w/ tongue

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Second leg has four 0.175 in. Min, 0.180 in. Maximum diameter holes equally spaced on 2.000 in. Diameter bolt circle

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.