

View Online at <https://aerobasegroup.com/nsn/5340-01-205-5930>

Mounting Hole Type:

Countersunk

First Leg Length:

1.620 inches

Second Leg Length:

2.090 inches

Second Leg Width:

5.750 inches

First Leg Hole Diameter:

Between 0.247 inches and 0.258 inches

Second Leg Hole Diameter:

Between 0.247 inches and 0.258 inches

Second Leg Distance Between Hole Centers Along Width:

3.070 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.630 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

3.500 inches

First Leg Corner Radius:

0.190 inches

First Leg Distance Between Hole Centers Along Width:

2.820 inches

First Leg Distance From Edge To Hole Center Along Width:

0.340 inches

First Leg Distance From Edge To Hole Center Along Length:

0.380 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Irregular shape

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 cl3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.