

View Online at <https://aerobasegroup.com/nsn/5340-01-205-9259>

Mounting Hole Type:

Countersunk and plain

First Leg Length:

2.000 inches

Second Leg Length:

2.000 inches

Second Leg Width:

13.500 inches

First Leg Hole Diameter:

Between 0.326 inches and 0.331 inches

Second Leg Distance Between Hole Centers Along Width:

5.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

Second Leg Slot Length:

0.500 inches

Second Leg Slot Width:

0.312 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

13.500 inches

First Leg Distance Between First And Second Hole Centers Along Width:

5.750 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

5.750 inches

First Leg Distance From Edge To Hole Center Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Six countersunk holes 0.096 in. Min, 0.101 in. Maximum dia, 100.0 degrees x 0.165 in.

Material:

Aluminum alloy 6061

Material Specification:

Ww-t-700/6 t6 federal specification single material response

Surface Treatment:

Paint

Surface Treatment Specification:

Cid std0985a0160 fscm 54497 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0