

View Online at <https://aerobasegroup.com/nsn/5340-01-206-2209>

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.250 inches

**Second Leg Length:**

3.190 inches

**Second Leg Width:**

13.190 inches

**First Leg Hole Diameter:**

0.531 inches

**Second Leg Hole Diameter:**

0.406 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

12.190 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

13.190 inches

**First Leg Distance Between Hole Centers Along Width:**

5.375 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.755 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**Second Leg Side Radius:**

1.000 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Side radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

2 mtg holes 0.281 in. Diameter on second leg; paint; color forrest green

**Material:**

Steel or steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

**Material Specification:**

Astm a283 assn standard 1st material response or astm a635 assn standard all material responses

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Mil-e-52798 military specification single treatment response or mil-e-52835 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-e-52798 spec.