

View Online at <https://aerobasegroup.com/nsn/5340-01-206-7039>

Center To Center Distance Between Bolt Holes Along Width:

2.625 inches

Center To Center Distance Between Bolt Holes Along Length:

3.625 inches

Wheel Quantity:

1

Safe Operating Load Rating:

360.0 pounds

Material And Location:

Steel wheel rim err-100 err-100 or iron, cast wheel rim err-100 err-100 or aluminum alloy wheel rim err-100 err-100

Surface Treatment And Location:

Cadmium wheel rim err-100 err-100 or zinc plated wheel rim err-100 err-100 or painted wheel rim err-100 err-100 or lacquer wheel rim err-100 err-100 or enamel wheel rim err-100 err-100

Wheel Type:

Built up

Wheel Diameter:

5.000 inches

Effective Height:

6.188 inches

Plate Style:

Rectangular

Wheel Bearing Type:

Roller or ball

Tread Width:

1.500 inches

Caster Plate Length:

4.750 inches

Caster Plate Width:

4.000 inches

Caster Plate Mounting Hole Diameter:

0.375 inches

Special Features:

No surface finish on aluminum casters; optional height 6.438 in.; optional mounting plate hole spacing 3.000 in. By 3.000 in.

Style Designator:

Rigid

Specification Or Standard:

A group and 1 type and 3 class and 7 style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A25600