

View Online at <https://aerobasegroup.com/nsn/5340-01-206-7039>

**Center To Center Distance Between Bolt Holes Along Width:**

2.625 inches

**Center To Center Distance Between Bolt Holes Along Length:**

3.625 inches

**Wheel Quantity:**

1

**Safe Operating Load Rating:**

360.0 pounds

**Material And Location:**

Steel wheel rim err-100 err-100 or iron, cast wheel rim err-100 err-100 or aluminum alloy wheel rim err-100 err-100

**Surface Treatment And Location:**

Cadmium wheel rim err-100 err-100 or zinc plated wheel rim err-100 err-100 or painted wheel rim err-100 err-100 or lacquer wheel rim err-100 err-100 or enamel wheel rim err-100 err-100

**Wheel Type:**

Built up

**Wheel Diameter:**

5.000 inches

**Effective Height:**

6.188 inches

**Plate Style:**

Rectangular

**Wheel Bearing Type:**

Roller or ball

**Tread Width:**

1.500 inches

**Caster Plate Length:**

4.750 inches

**Caster Plate Width:**

4.000 inches

**Caster Plate Mounting Hole Diameter:**

0.375 inches

**Special Features:**

No surface finish on aluminum casters; optional height 6.438 in.; optional mounting plate hole spacing 3.000 in. By 3.000 in.

**Style Designator:**

Rigid

**Specification Or Standard:**

A group and 1 type and 3 class and 7 style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A25600