

View Online at <https://aerobasegroup.com/nsn/5340-01-206-8601>

Mounting Hole Type:

Plain

First Leg Length:

63.5 millimeters

Second Leg Length:

63.5 millimeters

Second Leg Width:

64.0 millimeters

First Leg Hole Diameter:

10.3 millimeters

Second Leg Hole Diameter:

8.4 millimeters

Second Leg Distance Between Upper Hole Centers Along Width:

44.0 millimeters

Second Leg Distance Between Hole Centers Along Length:

20.0 major inches

Second Leg Distance Between First And Second Hole Centers Along Width:

22.0 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

10.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

21.5 millimeters

First Leg Thickness:

7.9 millimeters

Second Leg Thickness:

7.9 millimeters

First Leg Width:

64.0 millimeters

First Leg Distance Between Hole Centers Along Width:

40.0 millimeters

First Leg Distance Between Hole Centers Along Length:

23.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

12.0 millimeters

First Leg Distance From Edge To Hole Center Along Length:

16.5 millimeters

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

5.3 radians

Material:

Aluminum alloy

Surface Treatment:

Primer and paint

Surface Treatment Specification:

Mil-p-23377 military specification 1st treatment response and mil-c-46168 military specification 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-p-23377 spec.