NSN 5340-01-206-8601

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-206-8601 **Mounting Hole Type:** Plain First Leg Length: 63.5 millimeters Second Leg Length: 63.5 millimeters Second Leg Width: 64.0 millimeters First Leg Hole Diameter: 10.3 millimeters Second Leg Hole Diameter: 8.4 millimeters Second Leg Distance Between Upper Hole Centers Along Width: 44.0 millimeters Second Leg Distance Between Hole Centers Along Length: 20.0 major inches Second Leg Distance Between First And Second Hole Centers Along Width: 22.0 millimeters Second Leg Distance From Edge To Hole Center Along Width: 10.0 millimeters Second Leg Distance From Edge To Hole Center Along Length: 21.5 millimeters First Leg Thickness: 7.9 millimeters Second Leg Thickness: 7.9 millimeters First Leg Width: 64.0 millimeters First Leg Distance Between Hole Centers Along Width: 40.0 millimeters First Leg Distance Between Hole Centers Along Length: 23.0 millimeters First Leg Distance From Edge To Hole Center Along Width: 12.0 millimeters First Leg Distance From Edge To Hole Center Along Length: 16.5 millimeters First Leg Style: Square First Leg Hole Arrangement Style:

Two holes

Second Leg Style:
Square

NSN 5340-01-206-8601 Angle Bracket - Page 2 of 2



| Second Leg Hole Arrangement Style: |
|---|
| Three holes |
| Second Leg Relationship To First Leg: |
| Not identical |
| First Leg Angle: |
| 5.3 radians |
| Material: |
| Aluminum alloy |
| Surface Treatment: |
| Primer and paint |
| Surface Treatment Specification: |
| Mil-p-23377 military specification 1st treatment response and mil-c-46168 military specification 2nd treatment response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A042a0 |
| Mil-std (military Standard): |
| Mil-p-23377 spec. |
| |