

View Online at <https://aerobasegroup.com/nsn/5340-01-208-0335>

Mounting Hole Type:

Plain

First Leg Length:

1.310 inches

Second Leg Length:

4.000 inches

Reinforcement Method (non-core):

Gusset both sides

Second Leg Width:

1.880 inches

First Leg Slot Length:

0.530 inches

First Leg Slot Width:

Between 0.278 inches and 0.286 inches

Second Leg Hole Diameter:

Between 0.480 inches and 0.489 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.370 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

0.370 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.570 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

1.880 inches

First Leg Corner Radius:

0.120 inches

First Leg Distance Between Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.440 inches

First Leg Distance From Edge To Hole Center Along Length:

0.620 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

2 smaller holes second leg with 0.126 in. Min, 0.132 in. Maximum dia

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 t4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 type 1 cl 1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.