

View Online at <https://aerobasegroup.com/nsn/5340-01-210-3953>

Mounting Hole Type:

Plain

First Leg Length:

2.619 inches

Second Leg Length:

6.999 inches

Reinforcement Method (non-core):

Gusset both sides

Second Leg Width:

4.620 inches

First Leg Slot Length:

0.680 inches

First Leg Slot Width:

0.343 inches

Second Leg Distance Between Hole Centers Along Width:

3.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.950 inches

Second Leg Slot Length:

1.250 inches

Second Leg Slot Width:

0.500 inches

First Leg Thickness:

0.1196 inches

Second Leg Thickness:

0.1196 inches

First Leg Width:

4.620 inches

First Leg Distance Between Hole Centers Along Width:

2.620 inches

First Leg Distance From Edge To Hole Center Along Width:

0.565 inches

First Leg Distance From Edge To Hole Center Along Length:

0.620 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Cutout on first leg 1.250 in. Deep; cutout on second leg 3.810 in. Deep

Material:

Steel or steel comp 1009

Material Specification:

Astm a569 assn standard 1st material response or astm a109 assn standard 1st material response or astm a366 assn standard 2nd material response

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-52798 military specification single treatment response or mil-e-52835 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-e-52798 spec.