NSN 5340-01-210-7510

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-210-7510

Mounting Hole Type: Plain First Leg Length: 4.755 inches Second Leg Length: 6.215 inches Second Leg Width: 3.000 inches First Leg Hole Diameter: 0.656 inches Second Leg Hole Diameter: 0.406 inches Second Leg Distance Between Hole Centers Along Length: 3.000 inches Second Leg Distance From Edge To Hole Center Along Width: 0.860 inches **Second Leg Distance From Edge To Hole Center Along Length:** 0.500 inches First Leg Thickness: 0.375 inches Second Leg Thickness: 0.375 inches First Leg Width: 3.000 inches First Leg Distance Between Hole Centers Along Width: 1.500 inches First Leg Distance From Edge To Hole Center Along Width: 0.800 inches First Leg Distance From Edge To Hole Center Along Length: 0.940 inches First Leg Style: Square First Leg Hole Arrangement Style: Two holes Second Leg Style: Square **Second Leg Hole Arrangement Style:**

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

NSN 5340-01-210-7510

Angle Bracket - Page 2 of 2

Mil-e-52798 spec.



| Special Features: |
|--|
| Color forest green |
| Material: |
| Steel |
| Material Specification: |
| Astm a283 assn standard single material response or astm a36 assn standard single material response |
| Surface Treatment: |
| Enamel lusterless |
| Surface Treatment Specification: |
| Mil-e-52798 military specification single treatment response or mil-e-52835 military specification single treatment response |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A042a0 |
| Mil-std (military Standard): |