## NSN 5340-01-211-1182

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-211-1182

Mounting Hole Type:
Plain
First Leg Length:
1.000 inches
Second Leg Length:
1.250 inches
Second Leg Width:
8.000 inches
First Leg Hole Diameter:
Between 0.328 inches and 0.331 inches
Second Leg Distance Between Hole Centers Along Width:
7.625 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.188 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.250 inches
Second Leg Slot Length:
0.200 inches
Second Leg Slot Width:
0.140 inches
First Leg Thickness:
0.060 inches
Second Leg Thickness:
0.060 inches
First Leg Width:
8.000 inches
First Leg Distance Between Hole Centers Along Width:
4.000 inches
First Leg Distance From Edge To Hole Center Along Width:
3.000 inches
First Leg Distance From Edge To Hole Center Along Length:
0.312 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Cut out
Second Leg Hole Arrangement Style:
2 slots
Features Provided:
Retaining lug

## **NSN 5340-01-211-1182** Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Cutout Length:
0.560 inches
Second Leg Cutout Width:
6.500 inches
Special Features:
Right hand
Material:
Aluminum alloy 5052
Material Specification:
Qq-a-250/8, h32 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-f-14072, e512 military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-f-14072 spec.