

View Online at <https://aerobasegroup.com/nsn/5340-01-211-1183>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.000 inches

**Second Leg Length:**

1.250 inches

**Second Leg Width:**

8.000 inches

**First Leg Hole Diameter:**

Between 0.328 inches and 0.331 inches

**Second Leg Distance Between Hole Centers Along Width:**

7.625 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.188 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**Second Leg Slot Length:**

0.200 inches

**Second Leg Slot Width:**

0.140 inches

**First Leg Thickness:**

0.060 inches

**Second Leg Thickness:**

0.060 inches

**First Leg Width:**

8.000 inches

**First Leg Distance Between Hole Centers Along Width:**

4.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

3.000 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.312 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Cut out

**Second Leg Hole Arrangement Style:**

2 slots

**Features Provided:**

Retaining lug

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Cutout Length:**

0.560 inches

**Second Leg Cutout Width:**

6.500 inches

**Special Features:**

Left hand

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8, temp-h32 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-f-14072, e512 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-f-14072 spec.