NSN 5340-01-211-1481

Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-211-1481

view Offilite at https://defobasegroup.com/hsr//5040-01-211-1401
Thread Class:
2b left internal (includes through thread)
Thread Direction:
Right-hand left internal (includes through thread)
Thread Length:
0.9375 inches left internal (includes through thread)
Length:
0.9375 inches
Cross-sectional Shape:
Hexagon
Width Across Flats:
0.2500 inches
Thready Qty Per Inch (tpi):
40 left internal (includes through thread)
Thread Size:
0.1120 inches left internal (includes through thread)
Material:
Steel comp 203ez or steel comp 303 or steel comp 303 plus x or steel comp 303ma or steel comp 303pb or steel comp 303se or steel
comp 416 or steel comp 416 plus x or steel comp 416se or steel comp 430f or steel comp 440fse or steel comp 420f or steel comp
420fse or steel comp 440f
Material Specification:
Astm-a-581 assn standard single material response or astm-a-582 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072 military specification single treatment response or qq-p-35 federal specification single treatment response
Style Designator:
Internally threaded full length
Thread Series Designator:
Unc left internal (includes through thread)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-f-14072 spec.

Mil-std (military Standard):

A08900