

View Online at <https://aerobasegroup.com/nsn/5340-01-211-3060>

Mounting Hole Type:

Countersunk and plain

First Leg Length:

0.520 inches

Second Leg Length:

0.590 inches

Second Leg Width:

3.020 inches

First Leg Slot Length:

0.220 inches

First Leg Slot Width:

0.156 inches

Second Leg Hole Diameter:

Between 0.125 inches and 0.126 inches

Second Leg Distance Between Hole Centers Along Width:

2.040 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.174 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.158 inches

First Leg Thickness:

0.060 inches

Second Leg Thickness:

0.060 inches

First Leg Width:

3.020 inches

First Leg Distance Between Hole Centers Along Width:

2.188 inches

First Leg Distance From Edge To Hole Center Along Width:

0.682 inches

First Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Cutout Length:

0.520 inches

First Leg Cutout Width:

1.190 inches

Special Features:

Two spacers located on second leg

Material:

Aluminum alloy 6063

Material Specification:

Qq-a-200/9 t5 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.