

View Online at <https://aerobasegroup.com/nsn/5340-01-212-3115>

Mounting Hole Type:

Plain and countersunk

First Leg Length:

0.630 inches

Second Leg Length:

0.780 inches

Second Leg Width:

0.870 inches

Second Leg End Width:

0.630 inches

First Leg Hole Diameter:

0.173 inches

Second Leg Hole Diameter:

0.196 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.438 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

Center Section Height:

0.610 inches

Center Section Width:

0.870 inches

Center Section Thickness:

0.090 inches

First Leg Width:

0.870 inches

First Leg End Width:

0.630 inches

First Leg Distance Between Hole Centers Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

Heat treat to condition t6 per mfr ref hp1-2

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 federal specification single material response

Surface Treatment:

Oxide film

Surface Treatment Specification:

Epb4-230, n0.16 mfr ref single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0