

View Online at <https://aerobasegroup.com/nsn/5340-01-212-3115>

**Mounting Hole Type:**

Plain and countersunk

**First Leg Length:**

0.630 inches

**Second Leg Length:**

0.780 inches

**Second Leg Width:**

0.870 inches

**Second Leg End Width:**

0.630 inches

**First Leg Hole Diameter:**

0.173 inches

**Second Leg Hole Diameter:**

0.196 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.438 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.310 inches

**First Leg Thickness:**

0.090 inches

**Second Leg Thickness:**

0.090 inches

**Center Section Height:**

0.610 inches

**Center Section Width:**

0.870 inches

**Center Section Thickness:**

0.090 inches

**First Leg Width:**

0.870 inches

**First Leg End Width:**

0.630 inches

**First Leg Distance Between Hole Centers Along Width:**

0.375 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.310 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**First Leg Chamfer Angle:**

45.0 degrees

**Second Leg Chamfer Angle:**

45.0 degrees

**Special Features:**

Heat treat to condition t6 per mfr ref hp1-2

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 federal specification single material response

**Surface Treatment:**

Oxide film

**Surface Treatment Specification:**

Epb4-230, n0.16 mfr ref single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0