

View Online at <https://aerobasegroup.com/nsn/5340-01-212-6556>

Overall Height:

0.6250 inches

First Step Diameter:

Between 0.2850 inches and 0.2900 inches

First Step Length:

0.0800 inches

Second Step Diameter:

Between 0.5550 inches and 0.5600 inches

Second Step Length:

0.0700 inches

Third Step Diameter:

0.7500 inches

Bore Diameter:

Between 0.2010 inches and 0.2030 inches

End Application:

Flap cont roller, hyd

Material Hardness Rating:

Between 49.0 rockwell c and 53.0 rockwell c

Design Type:

Solid

End Diameter:

Between 0.2750 inches and 0.2800 inches

Distance From End To First Step:

0.4150 inches

Material:

Steel, qq-s-763

Material:

Steel comp 202 or steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp 633 or steel comp 634 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 430 or steel comp 430f or steel comp 430fse or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 440f or steel comp 440fse or steel comp 446

Material Specification:

Qq-s-763 federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ps13001, mcdonnell douglas corporation mfr ref single treatment response

Surface Treatment:

Passivated, ps13001, mcdonnell douglas corp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

T319-e