NSN 5340-01-212-8476

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-212-8476

First Leg Length:
2.000 inches
Second Leg Length:
6.750 inches
Second Leg Width:
14.250 inches
Second Leg End Width:
4.500 inches
First Leg Hole Diameter:
0.531 inches
Second Leg Hole Diameter:
0.531 inches
Second Leg Distance Between Hole Centers Along Width:
2.875 inches
Second Leg Distance Between First And Second Hole Centers Along Width:
5.875 inches
Second Leg Distance Between Second And Third Hole Centers Along Width:
2.935 inches
Second Leg Distance From Edge To Hole Center Along Width:
5.810 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.746 inches
Second Leg Distance Between First And Second Hole Centers Along Length:
1.874 inches
Second Leg Distance Between Second And Third Hole Centers Along Length:
0.188 inches
First Leg Thickness:
0.250 inches
Second Leg Thickness:
0.250 inches
First Leg Width:
14.250 inches
First Leg Distance Between Hole Centers Along Width:
12.750 inches
First Leg Distance From Edge To Hole Center Along Width:
0.750 inches
First Leg Distance From Edge To Hole Center Along Length:
0.750 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Two holes

NSN 5340-01-212-8476 Angle Bracket - Page 2 of 2



Se	econd Leg Style:
So	quare and tapered
Se	econd Leg Hole Arrangement Style:
Fo	bur holes
Se	econd Leg Relationship To First Leg:
N	ot identical
S	pecial Features:
Fi	nish coat-green 383; specification mil-c-46168; film thickness apply mil-std-193
М	aterial:
St	teel
М	aterial Specification:
Q	q-s-635 federal specification single material response
St	tyle Designator:
A	ngle
SI	helf Life:
N	/a
U	nit Of Measure:
D	emilitarization:
N	0
Fi	ig:
A	042a0
М	il-std (military Standard):
Μ	il-c-46168 spec.