

View Online at <https://aerobasegroup.com/nsn/5340-01-213-1353>

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.000 inches

**Second Leg Length:**

2.000 inches

**Second Leg Width:**

2.620 inches

**First Leg Hole Diameter:**

Between 0.406 inches and 0.410 inches

**Second Leg Hole Diameter:**

Between 0.406 inches and 0.410 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.625 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.750 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

2.620 inches

**First Leg Distance Between Hole Centers Along Width:**

1.625 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.750 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Color number 17875 white; do not paint holes

**Material:**

Aluminum alloy 5083 or aluminum alloy 5086 or aluminum alloy 5456 or aluminum alloy 6061

**Material Specification:**

Qq-a-200/4 federal specification 1st material response or qq-a-200/5 federal specification 2nd material response or qq-a-200/7 federal specification 3rd material response or qq-200/8 federal specification 4th material response or astm b308 assn standard 4th material response

**Surface Treatment:**

Plastic polyamide

**Surface Treatment Specification:**

Mil-c-22750, cl optional, type 1 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-22750 spec.