

View Online at <https://aerobasegroup.com/nsn/5340-01-213-1353>

Mounting Hole Type:

Plain

First Leg Length:

2.000 inches

Second Leg Length:

2.000 inches

Second Leg Width:

2.620 inches

First Leg Hole Diameter:

Between 0.406 inches and 0.410 inches

Second Leg Hole Diameter:

Between 0.406 inches and 0.410 inches

Second Leg Distance Between Hole Centers Along Width:

1.625 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

2.620 inches

First Leg Distance Between Hole Centers Along Width:

1.625 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Special Features:

Color number 17875 white; do not paint holes

Material:

Aluminum alloy 5083 or aluminum alloy 5086 or aluminum alloy 5456 or aluminum alloy 6061

Material Specification:

Qq-a-200/4 federal specification 1st material response or qq-a-200/5 federal specification 2nd material response or qq-a-200/7 federal specification 3rd material response or qq-200/8 federal specification 4th material response or astm b308 assn standard 4th material response

Surface Treatment:

Plastic polyamide

Surface Treatment Specification:

Mil-c-22750, cl optional, type 1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-22750 spec.