NSN 5340-01-213-5468

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-213-5468

Mounting Hole Type:
Plain

0.500 inches

Second Leg Length:

First Leg Length:

1.000 inches

Second Leg Width:

1.800 inches

First Leg Hole Diameter:

Between 0.213 inches and 0.216 inches

Second Leg Hole Diameter:

Between 0.172 inches and 0.175 inches

Second Leg Distance Between Hole Centers Along Width:

1.496 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.152 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

1.800 inches

First Leg Distance Between Hole Centers Along Width:

1.400 inches

First Leg Distance From Edge To Hole Center Along Width:

0.200 inches

First Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

NSN 5340-01-213-5468

Angle Bracket - Page 2 of 2



Special Features:

Long leg notched 0.600 in. W by 0.888 in. Lg with two 0.090 in. Internal radiused corners; two fasteners, self locking, spline p/n 929339-2, fscm 49956 are pressed into leg segments on both sides of notch; short leg has two fasteners, self locking, spline p/n 929339-4, fscm 49956 pressed into 1.400 mounting centers; all flanges of fsateners are on the inside faces of the bracket

R 4	at	!		١.
IVI	ЭΤ	-	ıaı	ľ

Aluminum alloy 6063

Material Specification:

Qq-a-200, t52 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.