

View Online at <https://aerobasegroup.com/nsn/5340-01-215-0149>

**Mounting Hole Type:**

Plain

**End Application:**

W/s: missile, air launch cruise (alcm) agm-86b; engine, aircraft, tf-33-p-7 (c-141a/b); u-2 engine (f-118-ge-101); engine, f118-ge-100 (b-2 bomber); engine, aircraft, f110-ge-100/129 (f-16 c/d); engine, aircraft, f-108 (cfm-56, kc-135a); engine, aircraft f110-ge-400

**First Leg Hole Diameter:**

Between 0.337 inches and 0.351 inches

**Second Leg Hole Diameter:**

Between 0.274 inches and 0.288 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.150 inches

**First Leg Thickness:**

Between 0.060 inches and 0.066 inches

**Second Leg Thickness:**

Between 0.060 inches and 0.066 inches

**First Leg Distance Between Hole Centers Along Width:**

1.088 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Hole Arrangement Style:**

Two holes

**Features Provided:**

Nut

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Furnished with 2 nutplates (item 2); each nutplate has floating nut and 2 rivet holes, 0.098 in. Min, 0.102 in. Maximum dia, and 4 rivets (item 3), 2 for each nutplate

**Material:**

Nickel alloy 625

**Material Specification:**

Ams 5599 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0