

View Online at <https://aerobasegroup.com/nsn/5340-01-215-0149>

Mounting Hole Type:

Plain

End Application:

W/s: missile, air launch cruise (alcm) agm-86b; engine, aircraft, tf-33-p-7 (c-141a/b); u-2 engine (f-118-ge-101); engine, f118-ge-100 (b-2 bomber); engine, aircraft, f110-ge-100/129 (f-16 c/d); engine, aircraft, f-108 (cfm-56, kc-135a); engine, aircraft f110-ge-400

First Leg Hole Diameter:

Between 0.337 inches and 0.351 inches

Second Leg Hole Diameter:

Between 0.274 inches and 0.288 inches

Second Leg Distance Between Hole Centers Along Length:

1.150 inches

First Leg Thickness:

Between 0.060 inches and 0.066 inches

Second Leg Thickness:

Between 0.060 inches and 0.066 inches

First Leg Distance Between Hole Centers Along Width:

1.088 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Hole Arrangement Style:

Two holes

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Furnished with 2 nutplates (item 2); each nutplate has floating nut and 2 rivet holes, 0.098 in. Min, 0.102 in. Maximum dia, and 4 rivets (item 3), 2 for each nutplate

Material:

Nickel alloy 625

Material Specification:

Ams 5599 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0