

View Online at <https://aerobasegroup.com/nsn/5340-01-215-2855>

Mounting Hole Diameter:

0.128 inches

Center To Center Distance Between Mounting Holes Along Width:

Between 1.062 inches and 1.067 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 0.906 inches and 0.911 inches

Lever Offset Distance:

0.080 inches

Bolt Offset Distance:

0.080 inches

Special Features:

Between mounting base length: 1.218 in. And 1.223 in. ; mounting base width: 1.374 in. And 1.379 in. ; button trigger material: aluminum alloy per qq-a-250/4, alloy 2024 or per qq-a-225/6; gasket material: synthetic rubber per ams 3240; screw material: steel per ams 5643; button bolt material and washer material: aluminum alloy per qq-a-250/4, alloy 2024; channel and link material: steel 302; button trigger, button bolt, and washer: anodized per mil-a-8625, type 2; screw, channel, and link passivated per qq-p-35

Material:

Steel comp 631 spring

Material Specification:

Ams 5673 assn standard single material response spring

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spring

Style Designator:

Button actuator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A10600

Mil-std (military Standard):

Mil-s-5059 spec.