

View Online at <https://aerobasegroup.com/nsn/5340-01-215-2855>

**Mounting Hole Diameter:**

0.128 inches

**Center To Center Distance Between Mounting Holes Along Width:**

Between 1.062 inches and 1.067 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 0.906 inches and 0.911 inches

**Lever Offset Distance:**

0.080 inches

**Bolt Offset Distance:**

0.080 inches

**Special Features:**

Between mounting base length: 1.218 in. And 1.223 in. ; mounting base width: 1.374 in. And 1.379 in. ; button trigger material: aluminum alloy per qq-a-250/4, alloy 2024 or per qq-a-225/6; gasket material: synthetic rubber per ams 3240; screw material: steel per ams 5643; button bolt material and washer material: aluminum alloy per qq-a-250/4, alloy 2024; channel and link material: steel 302; button trigger, button bolt, and washer: anodized per mil-a-8625, type 2; screw, channel, and link passivated per qq-p-35

**Material:**

Steel comp 631 spring

**Material Specification:**

Ams 5673 assn standard single material response spring

**Surface Treatment:**

Passivate spring

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spring

**Style Designator:**

Button actuator

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A10600

**Mil-std (military Standard):**

Mil-s-5059 spec.