

View Online at <https://aerobasegroup.com/nsn/5340-01-215-9219>

Mounting Hole Type:

Plain and countersunk

First Leg Length:

1.250 inches

Second Leg Length:

1.250 inches

First Leg Hole Diameter:

Between 0.141 inches and 0.147 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

Center Section Height:

2.120 inches

Center Section Width:

2.000 inches

Center Section Thickness:

0.063 inches

First Leg Width:

2.000 inches

First Leg Corner Radius:

0.120 inches

First Leg Distance Between Hole Centers Along Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

2nd hole each leg csk 0.134 in. Min and 0.138 in. Maximum dia; ctr sect hole 1.500 in. Diameter and 2 holes 0.206 in. Min and 0.212 in. Maximum dia; 2 slots on each leg 0.219 in. Lg by 0.256 in. Wd

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 h-32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 cl 1 or 3 military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.