NSN 5340-01-217-4069

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-217-4069

view Online at https://aerobasegroup.com/nsn/5340-01-217-4069
Mounting Hole Type:
Plain
First Leg Length:
3.000 inches
Second Leg Length:
5.000 inches
Second Leg Width:
Between 5.970 inches and 6.030 inches
First Leg Slot Length:
Between 0.735 inches and 0.765 inches
First Leg Slot Width:
Between 0.990 inches and 1.020 inches
Second Leg Hole Diameter:
0.531 inches
Second Leg Distance Between Hole Centers Along Width:
4.000 inches
Second Leg Distance Between Hole Centers Along Length:
2.000 inches
Second Leg Distance From Edge To Hole Center Along Width:
1.000 inches
Second Leg Distance From Edge To Hole Center Along Length:
1.000 inches
First Leg Thickness:
0.437 inches
Second Leg Thickness:
0.437 inches
First Leg Width:
Between 5.970 inches and 6.030 inches
First Leg Distance Between Hole Centers Along Width:
4.000 inches
First Leg Distance From Edge To Hole Center Along Width:
1.000 inches
First Leg Distance From Edge To Hole Center Along Length:
1.250 inches
1.250 III01165
First Leg Style:
First Leg Style:
First Leg Style: Square
First Leg Style: Square First Leg Hole Arrangement Style:
First Leg Style: Square First Leg Hole Arrangement Style: 2 slots
First Leg Style: Square First Leg Hole Arrangement Style: 2 slots Second Leg Style:

Four holes

NSN 5340-01-217-4069

Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Material:
Steel
Material Specification:
Astm a36 assn standard single material response or qq-s-741 federal specification single material response
Surface Treatment:
Primer epoxy
Surface Treatment Specification:
Mil-p-52192 military specification single treatment response or mil-p-53022 military specification single treatment response or mil-p-53030
military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-p-52192 spec.