

View Online at <https://aerobasegroup.com/nsn/5340-01-217-4069>

Mounting Hole Type:

Plain

First Leg Length:

3.000 inches

Second Leg Length:

5.000 inches

Second Leg Width:

Between 5.970 inches and 6.030 inches

First Leg Slot Length:

Between 0.735 inches and 0.765 inches

First Leg Slot Width:

Between 0.990 inches and 1.020 inches

Second Leg Hole Diameter:

0.531 inches

Second Leg Distance Between Hole Centers Along Width:

4.000 inches

Second Leg Distance Between Hole Centers Along Length:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Thickness:

0.437 inches

Second Leg Thickness:

0.437 inches

First Leg Width:

Between 5.970 inches and 6.030 inches

First Leg Distance Between Hole Centers Along Width:

4.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Length:

1.250 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel

Material Specification:

Astm a36 assn standard single material response or qq-s-741 federal specification single material response

Surface Treatment:

Primer epoxy

Surface Treatment Specification:

Mil-p-52192 military specification single treatment response or mil-p-53022 military specification single treatment response or mil-p-53030 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-p-52192 spec.