

View Online at <https://aerobasegroup.com/nsn/5340-01-217-4679>

**Mounting Hole Type:**

Plain and countersunk

**First Leg Length:**

2.340 inches

**Second Leg Length:**

4.190 inches

**Reinforcement Method (non-core):**

Gusset both sides

**Second Leg Width:**

5.380 inches

**First Leg Hole Diameter:**

Between 0.183 inches and 0.190 inches

**First Leg Thickness:**

0.090 inches

**Second Leg Thickness:**

0.090 inches

**First Leg Width:**

5.380 inches

**First Leg Distance Between Upper Hole Centers Along Width:**

5.000 inches

**First Leg Distance Between Lower Hole Centers Along Width:**

4.656 inches

**First Leg Distance Between Hole Centers Along Length:**

1.859 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

0.172 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.190 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.311 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Four holes

**Second Leg Style:**

Square

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Second leg has 3 holes 0.159 in. Dia; 1 hole 1.000 in. Dia; 2 holes tapped for 0.250-28 unf 2b helical insert

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11, t6 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.