

View Online at <https://aerobasegroup.com/nsn/5340-01-217-4679>

Mounting Hole Type:

Plain and countersunk

First Leg Length:

2.340 inches

Second Leg Length:

4.190 inches

Reinforcement Method (non-core):

Gusset both sides

Second Leg Width:

5.380 inches

First Leg Hole Diameter:

Between 0.183 inches and 0.190 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

5.380 inches

First Leg Distance Between Upper Hole Centers Along Width:

5.000 inches

First Leg Distance Between Lower Hole Centers Along Width:

4.656 inches

First Leg Distance Between Hole Centers Along Length:

1.859 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.172 inches

First Leg Distance From Edge To Hole Center Along Width:

0.190 inches

First Leg Distance From Edge To Hole Center Along Length:

0.311 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Second leg has 3 holes 0.159 in. Dia; 1 hole 1.000 in. Dia; 2 holes tapped for 0.250-28 unf 2b helical insert

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11, t6 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.