NSN 5340-01-217-9424

Swivel Caster - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-217-9424

Center To Center Distance Between Bolt Holes Along Width:
1.750 inches
Center To Center Distance Between Bolt Holes Along Length:
2.875 inches
Wheel Quantity:
1
Safe Operating Load Rating:
225.0 pounds
Material And Location:
Rubber, composition tread
Surface Treatment And Location:
Zinc plated plate
Wheel Type:
Built up
Wheel Diameter:
3.500 inches
Effective Height:
4.812 inches
Plate Style:
Rectangular
Wheel Bearing Type:
Wheel Bearing Type: Sleeve
Sleeve
Sleeve Swivel Bearing Type:
Sleeve Swivel Bearing Type: Annular ball
Sleeve Swivel Bearing Type: Annular ball Swivel Bearing Arrangement:
Sleeve Swivel Bearing Type: Annular ball Swivel Bearing Arrangement: Two row
Sleeve Swivel Bearing Type: Annular ball Swivel Bearing Arrangement: Two row Tread Width:
Sleeve Swivel Bearing Type: Annular ball Swivel Bearing Arrangement: Two row Tread Width: 3.500 inches
Sleeve Swivel Bearing Type: Annular ball Swivel Bearing Arrangement: Two row Tread Width: 3.500 inches Caster Plate Length:
Sleeve Swivel Bearing Type: Annular ball Swivel Bearing Arrangement: Two row Tread Width: 3.500 inches Caster Plate Length: 3.750 inches
Sleeve Swivel Bearing Type: Annular ball Swivel Bearing Arrangement: Two row Tread Width: 3.500 inches Caster Plate Length: 3.750 inches Caster Plate Width:
Sleeve Swivel Bearing Type: Annular ball Swivel Bearing Arrangement: Two row Tread Width: 3.500 inches Caster Plate Length: 3.750 inches Caster Plate Width: 2.750 inches
Sleeve Swivel Bearing Type: Annular ball Swivel Bearing Arrangement: Two row Tread Width: 3.500 inches Caster Plate Length: 3.750 inches Caster Plate Width: 2.750 inches Caster Plate Mounting Hole Diameter:
Sleeve Swivel Bearing Type: Annular ball Swivel Bearing Arrangement: Two row Tread Width: 3.500 inches Caster Plate Length: 3.750 inches Caster Plate Width: 2.750 inches Caster Plate Mounting Hole Diameter: 0.344 inches
Sleeve Swivel Bearing Type: Annular ball Swivel Bearing Arrangement: Two row Tread Width: 3.500 inches Caster Plate Length: 3.750 inches Caster Plate Width: 2.750 inches Caster Plate Mounting Hole Diameter: 0.344 inches Special Features:
Sleeve Swivel Bearing Type: Annular ball Swivel Bearing Arrangement: Two row Tread Width: 3.500 inches Caster Plate Length: 3.750 inches Caster Plate Width: 2.750 inches Caster Plate Mounting Hole Diameter: 0.344 inches Special Features: 2 holes in top plate are slotted; toe brake
Sleeve Swivel Bearing Type: Annular ball Swivel Bearing Arrangement: Two row Tread Width: 3.500 inches Caster Plate Length: 3.750 inches Caster Plate Width: 2.750 inches Caster Plate Mounting Hole Diameter: 0.344 inches Special Features: 2 holes in top plate are slotted; toe brake Style Designator:
Sleeve Swivel Bearing Type: Annular ball Swivel Bearing Arrangement: Two row Tread Width: 3.500 inches Caster Plate Length: 3.750 inches Caster Plate Width: 2.750 inches Caster Plate Mounting Hole Diameter: 0.344 inches Special Features: 2 holes in top plate are slotted; toe brake Style Designator: Swivel offset

-

NSN 5340-01-217-9424

Swivel Caster - Page 2 of 2



Demilitarization:

No

Fiig:

A25600