

View Online at <https://aerobasegroup.com/nsn/5340-01-218-7160>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.250 inches

**Second Leg Length:**

1.380 inches

**Second Leg Width:**

0.750 inches

**First Leg Hole Diameter:**

Between 0.406 inches and 0.436 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.380 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.410 inches

**Second Leg Slot Length:**

Between 0.465 inches and 0.495 inches

**Second Leg Slot Width:**

Between 0.385 inches and 0.415 inches

**First Leg Thickness:**

0.0598 inches

**Second Leg Thickness:**

0.0598 inches

**First Leg Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.380 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.410 inches

**First Leg End Radius:**

0.500 inches

**Second Leg End Radius:**

0.500 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1009

**Material Specification:**

Astm a366 assn standard single material response or astm a569 assn standard single material response

**Surface Treatment:**

Cadmium and chromate or zinc and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 1 federal specification 1st treatment response or astm b633, type 2 assn standard 2nd treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0