NSN 5340-01-219-3026

Double Angle Bracket - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5340-01-219-3026 |
|---|
| Mounting Hole Type: |
| Plain |
| End Application: |
| W/s: missile, air launch cruise (alcm) agm-86b; engine, aircraft, f110-ge-100/129 (f-16 c/d) |
| First Leg Hole Diameter: |
| Between 0.274 inches and 0.288 inches |
| Second Leg Hole Diameter: |
| Between 0.274 inches and 0.288 inches |
| Second Leg Distance Between Hole Centers Along Width: |
| 0.749 inches |
| First Leg Thickness: |
| Between 0.060 inches and 0.066 inches |
| Second Leg Thickness: |
| Between 0.060 inches and 0.066 inches |
| Center Section Thickness: |
| Between 0.060 inches and 0.066 inches |
| First Leg Style: |
| End radius |
| First Leg Hole Arrangement Style: |
| One hole |
| Second Leg Style: |
| Corner radius |
| Second Leg Hole Arrangement Style: |
| Two holes |
| Features Provided: |
| Nut |
| Second Leg Relationship To First Leg: |
| Not identical |
| First Leg Angle: |
| Between 89.0 degrees and 91.0 degrees |
| Second Leg Angle: |
| Between 89.0 degrees and 91.0 degrees |
| Special Features: |
| Three plate nuts riveted on, three holes 0.337 in. Min and 0.351 in. Maximum diameter on center section |
| Material: |
| Nickel alloy 625 |
| Material Specification: |
| Ams 5599 assn standard single material response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5340-01-219-3026

Double Angle Bracket - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A042a0