

View Online at <https://aerobasegroup.com/nsn/5340-01-219-3932>

Center To Center Distance Between Bolt Holes Along Width:

2.438 inches

Center To Center Distance Between Bolt Holes Along Length:

4.938 inches

Wheel Quantity:

1

Safe Operating Load Rating:

670.0 pounds

Material And Location:

Steel wheel rim err-100 err-100 or iron wheel rim err-100 err-100 or aluminum alloy wheel rim err-100 err-100

Surface Treatment And Location:

Cadmium plate or zinc plated plate or painted plate or lacquer plate or enamel plate

Wheel Type:

Built up

Wheel Diameter:

8.000 inches

Effective Height:

10.250 inches

Features Provided:

Swivel lubrication fitting

Plate Style:

Rectangular

Wheel Bearing Type:

Roller or ball

Swivel Bearing Type:

Annular ball

Swivel Bearing Arrangement:

Two row or two level

Tread Width:

2.500 inches

Caster Plate Length:

7.000 inches

Caster Plate Width:

5.000 inches

Caster Plate Mounting Hole Diameter:

0.500 inches

Special Features:

No surface finish on aluminum casters; optional height 10.620 in.; optional mounting plate hole spacing 3.375 in. By 5.250 in.

Style Designator:

Swivel offset

Specification Or Standard:

A group and 2 type and 5 class and 2 style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A25600