

View Online at <https://aerobasegroup.com/nsn/5340-01-219-3932>

**Center To Center Distance Between Bolt Holes Along Width:**

2.438 inches

**Center To Center Distance Between Bolt Holes Along Length:**

4.938 inches

**Wheel Quantity:**

1

**Safe Operating Load Rating:**

670.0 pounds

**Material And Location:**

Steel wheel rim err-100 err-100 or iron wheel rim err-100 err-100 or aluminum alloy wheel rim err-100 err-100

**Surface Treatment And Location:**

Cadmium plate or zinc plated plate or painted plate or lacquer plate or enamel plate

**Wheel Type:**

Built up

**Wheel Diameter:**

8.000 inches

**Effective Height:**

10.250 inches

**Features Provided:**

Swivel lubrication fitting

**Plate Style:**

Rectangular

**Wheel Bearing Type:**

Roller or ball

**Swivel Bearing Type:**

Annular ball

**Swivel Bearing Arrangement:**

Two row or two level

**Tread Width:**

2.500 inches

**Caster Plate Length:**

7.000 inches

**Caster Plate Width:**

5.000 inches

**Caster Plate Mounting Hole Diameter:**

0.500 inches

**Special Features:**

No surface finish on aluminum casters; optional height 10.620 in.; optional mounting plate hole spacing 3.375 in. By 5.250 in.

**Style Designator:**

Swivel offset

**Specification Or Standard:**

A group and 2 type and 5 class and 2 style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A25600