

View Online at <https://aerobasegroup.com/nsn/5340-01-219-7274>

Mounting Hole Type:

Plain

First Leg Length:

2.000 inches

Second Leg Length:

2.000 inches

Second Leg Width:

2.000 inches

First Leg Hole Diameter:

Between 0.326 inches and 0.333 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

8.625 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

8.625 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.750 inches

Second Leg Slot Length:

0.750 inches

Second Leg Slot Width:

0.312 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

2.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

8.625 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

8.625 inches

First Leg Distance From Edge To Hole Center Along Width:

1.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

3 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Three nut plates riveted to first leg

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-200/8, t6 federal specification single material response

Surface Treatment:

Paint

Surface Treatment Specification:

Cid standard 0985a0160, fscm 54497 mfr ref single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0