NSN 5340-01-220-0342

Webbing Strap - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-220-0342

Width:
1.000 inches
Length:
Between 29.100 inches and 30.900 inches
Environmental Protection:
Heat resistant and moisture resistant
Loop Style Designator:
Flat
End Type:
Folded and w/attachment
Hook Quantity:
1
Hook Material:
Steel, mil-s-6758, comp 4130
Attachment Method For Which Designed:
Sewed
Buckle Material:
Zinc alloy, qq-z-363 and steel, astm a568, comp 1020
Buckle Location:
4.880 in. Min 5.150 in. Maximum from end
Fastened Buckle Feature:
Not included
Buckle Fastening Method:
Friction
Fold Type:
Tight
Hook Connection Type:
Swiveling
Fastened Hook Feature:
Included
Hook Fastening Method:
Sewed
Loop Material:
Steel, astm a568, comp 1020
Fastened Loop Feature:
Included
Loop Fastening Method:
Sewed
Loop Location:
First loop 4.880 in. Min 5.150 in. Maximum from end, second loop 29.100 in. Min 30.900 in. Maximum from end
End Attachment/fastening Facility:
Loop

NSN 5340-01-220-0342

Webbing Strap - Page 2 of 2



۰.		:~1		4	res	
OL.	Jec	ıaı	eа	tu	res	١.

Both loops case-hardened and cadmium plated per federal specification qq-p-416; 6 in. Long buckle guard attachedto strap

Color:

Gray, federal standard 595, 36270

Material:

Nylon

Material:

Plastic polyamide

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T372-b