

View Online at <https://aerobasegroup.com/nsn/5340-01-221-8736>

Mounting Hole Type:

Countersunk and plain

First Leg Length:

0.995 inches

Second Leg Length:

1.000 inches

Reinforcement Method (non-core):

Turned edge center section

Second Leg Width:

5.525 inches

First Leg Hole Diameter:

Between 0.123 inches and 0.129 inches

Second Leg Hole Diameter:

Between 0.221 inches and 0.226 inches

Second Leg Distance Between Hole Centers Along Width:

3.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.400 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Height:

12.300 inches

Center Section Width:

4.950 inches

Center Section Thickness:

0.125 inches

First Leg Width:

5.525 inches

First Leg Distance Between Hole Centers Along Width:

3.550 inches

First Leg Distance From Edge To Hole Center Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Length:

0.320 inches

First Leg Style:

Cut out

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

First Leg Cutout Length:

0.620 inches

First Leg Cutout Width:

3.300 inches

Special Features:

1 slot 4.350 in. W by 11.050 in. Lg located on c section, 3 holes 0.154 in. Min and 0.161 in. Maximum diameter located on c section, 12 holes 0.098 in. Min and 0.103 in. Maximum diameter located on turned edge

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h34 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.