Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-223-2116

F	irst Leg Length:
0.	.797 inches
S	econd Leg Length:
3.	.130 inches
S	econd Leg Width:
1.	.000 inches
S	econd Leg End Width:
0.	.750 inches
F	irst Leg Hole Diameter:
В	etween 0.249 inches and 0.251 inches
S	econd Leg Hole Diameter:
0.	.156 inches
S	econd Leg Distance Between Hole Centers Along Length:
1.	.100 inches
S	econd Leg Distance From Edge To Hole Center Along Width:
0.	.328 inches
S	econd Leg Distance From Edge To Hole Center Along Length:
0.	.280 inches
S	econd Leg Distance Between First And Second Hole Centers Along Length:
0.	.660 inches
S	econd Leg Distance Between Second And Third Hole Centers Along Length:
0.	.650 inches
F	irst Leg Thickness:
0.	.080 inches
S	econd Leg Thickness:
0.	.080 inches
F	irst Leg Width:
1.	.000 inches
F	irst Leg Distance From Edge To Hole Center Along Width:
0.	.600 inches
F	irst Leg Distance From Edge To Hole Center Along Length:
0.	.377 inches
F	irst Leg Style:
S	quare
F	irst Leg Hole Arrangement Style:
0	one hole
S	econd Leg Hole Arrangement Style:
F	our holes
S	econd Leg Relationship To First Leg:
Ν	lot identical
F	irst Leg Angle:
0.	.12 radians

NSN 5340-01-223-2116

Angle Bracket - Page 2 of 2



Special Features:

Fourth hole on second leg 0.125 in. Dia, fourth hole offset 0.420 in. From edge

Material:

Steel comp 4130

Material Specification:

Mil-s-18729, cond a military specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-18729 spec.