

View Online at <https://aerobasegroup.com/nsn/5340-01-223-2652>

Mounting Hole Type:

Plain and threaded

First Leg Length:

4.000 inches

Second Leg Length:

6.380 inches

Second Leg Width:

5.755 inches

Second Leg End Width:

4.255 inches

First Leg Slot Length:

Between 0.876 inches and 0.938 inches

First Leg Slot Width:

Between 0.656 inches and 0.700 inches

Second Leg Hole Diameter:

Between 2.575 inches and 2.585 inches

Second Leg Distance Between Hole Centers Along Width:

2.347 inches

Second Leg Distance Between Hole Centers Along Length:

2.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

3.130 inches

First Leg Thickness:

0.625 inches

Second Leg Thickness:

1.000 inches

First Leg Width:

4.750 inches

First Leg Distance Between Hole Centers Along Width:

3.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.875 inches

First Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Special Features:

2nd leg, 1 hole 0.628 in. Min and 0.672 in. Maximum diameter and 0.125 in. Min and 0.156 in. Maximum diameter through hole; 0.250-20 unc 2b thread size two holes one on each leg

Material:

Steel

Material Specification:

Qq-s-741 military specification single material response or mil-s-22141 comp ic1020 or ic1030 military specification single material response

Surface Treatment:

Enamel or enamel lusterless

Surface Treatment Specification:

Mil-e-52798 military specification single treatment response or mil-e-52835 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-s-22141 spec.