

View Online at <https://aerobasegroup.com/nsn/5340-01-224-1503>

**Mounting Hole Type:**

Plain and threaded

**First Leg Length:**

0.522 inches

**Second Leg Length:**

0.582 inches

**Second Leg Width:**

1.040 inches

**First Leg Slot Length:**

0.260 inches

**First Leg Slot Width:**

0.156 inches

**Second Leg Hole Diameter:**

0.860 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.800 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.120 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.150 inches

**First Leg Thickness:**

0.062 inches

**Second Leg Thickness:**

0.062 inches

**First Leg Width:**

1.600 inches

**First Leg End Width:**

1.100 inches

**First Leg Distance Between Hole Centers Along Width:**

0.620 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.190 inches

**First Leg Style:**

Angle

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Cut out

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

118.0 degrees

**Second Leg Cutout Length:**

0.400 inches

**Second Leg Cutout Width:**

0.640 inches

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8, h32 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 3 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.