

View Online at <https://aerobasegroup.com/nsn/5340-01-224-1503>

Mounting Hole Type:

Plain and threaded

First Leg Length:

0.522 inches

Second Leg Length:

0.582 inches

Second Leg Width:

1.040 inches

First Leg Slot Length:

0.260 inches

First Leg Slot Width:

0.156 inches

Second Leg Hole Diameter:

0.860 inches

Second Leg Distance Between Hole Centers Along Width:

0.800 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.120 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.150 inches

First Leg Thickness:

0.062 inches

Second Leg Thickness:

0.062 inches

First Leg Width:

1.600 inches

First Leg End Width:

1.100 inches

First Leg Distance Between Hole Centers Along Width:

0.620 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.190 inches

First Leg Style:

Angle

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

118.0 degrees

Second Leg Cutout Length:

0.400 inches

Second Leg Cutout Width:

0.640 inches

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8, h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.